


# Domestic and Commercial Thermostatic Radiator Valves (TRVs)



# About Resideo

Resideo is a leading global manufacturer and distributor of technology-driven products and solutions that provide comfort, security, energy efficiency and control to customers worldwide. Building on a 130-year heritage, Resideo has a presence in more than 150 million homes, with 15 million systems installed in homes each year.


We operate a number of research and development, and manufacturing locations throughout the UK and Europe. These long-established facilities are committed to supplying you with leading-edge technology and first-class products.

**PROUD TO BE  
MANUFACTURED  
IN THE UK & EUROPE**



## Thermostatic Radiator Valves (TRVs)

TRVs provide local control of room temperatures to maintain comfort and save energy. TRVs sense the air temperature around them and control the flow of water through the radiator to which they are fitted, to maintain and limit the temperature within the room.



## Contents

|                                 |              |
|---------------------------------|--------------|
| <b>TRVs</b>                     | <b>4-5</b>   |
| Domestic TRVs                   | 4            |
| Manual Radiator Valve Pack      | 4            |
| Designer TRV Heads              | 5            |
| <b>PRESSURE INDEPENDENT TRV</b> | <b>6-7</b>   |
| <b>BALANCING</b>                | <b>8-9</b>   |
| <b>EVOHOME SMART TRVs</b>       | <b>10-11</b> |
| <b>COMMERCIAL TRVs</b>          | <b>12-14</b> |
| Low Flow                        | 12           |
| Standard Flow                   | 12           |
| High Flow                       | 12           |
| Capri Head                      | 13           |
| Verafix lockshield              | 13           |
| Tamper proof head               | 13           |
| Robust TRV Head                 | 14           |
| Remote TRV Head                 | 14           |
| <b>TRAINING</b>                 | <b>15</b>    |
| <b>REGULATIONS</b>              | <b>15</b>    |
| <b>PRODUCT CODE SELECTOR</b>    | <b>16-19</b> |



# TRVs

## DOMESTIC TRVS



VTL15

- Bi-directional flow design
- Can be mounted vertically or horizontally at either end of the radiator
- Integrated radiator balancing insert
- 6 mm of play on radiator tail piece to allow for variation in radiator distance from valve
- Wax sensor provides consistent and reliable performance
- Range stops included in head
- The insert can be removed and replaced without draining down



VTL120

- Bi-directional flow design
- TELL, EN215 & Keymark certified for 'A' rated efficiency
- Can be mounted vertically or horizontally
- Integrated radiator balancing insert
- Easy grip TRV head with energy saving button that alerts user to economical setting for comfort
- Liquid sensor provides consistent and long-lasting performance
- Frost setting
- 6 mm play on radiator tailpiece to allow for variation in radiator distance from the valve
- Push fit options are available



VTL200

- Bi-directional flow design
- TELL, EN215 & Key mark certified for 'A' rated efficiency
- Can be mounted vertically or horizontally
- Integrated radiator balancing insert
- Frost setting
- Stylish TRV design with different finish options
- Liquid sensor provides consistent and long-lasting performance
- 6 mm play on radiator tailpiece to allow for variation in radiator distance from valve
- Push fit options are available

## MANUAL RADIATOR VALVE PACK

Using the manual radiator valve pack ensures you can visually match with our TRV heads. The manual valve allows the user to switch the radiator on/off, and the lockshield valve limits water flow through individual radiators in wet central heating systems. The valves can be mounted vertically or horizontally at either end of a radiator.

- Bi-directional flow design
- Positive shut off
- The insert can be removed and replaced without draining down



VHL120

## DESIGNER TRV HEADS

Match the TRV head to the decor of the room – easily interchangeable heads available as accessory packs. Will fit all Honeywell Home TRV bodies and many non-Honeywell Home TRVs.



T4221GB  
Polished Chrome



T4111GB  
Brushed Chrome



T4321GB  
Black & Chrome



T4021GB  
White & Chrome



# Pressure Independent TRV

## KOMBI TRV

### V2100



The Kombi TRV is a thermostatic radiator valve with an inbuilt differential pressure controller. This combination of two valves in one ensures optimal room temperature control and easy automatic hydronic balancing. Piping and pressure loss calculations are not needed, it requires only the max design flow to be set directly on the Kombi TRV.

Unlike standard TRV operation, the inbuilt pressure controller ensures that the max flow is maintained under varying system pressure conditions, simply and easily, eliminating common unbalanced heating systems.

Available for selection on the Honeywell Home TRV balancing app.


### Features and benefits

- Automatic hydronic balancing – only needs to be installed on each radiator
- No need for complex piping and pressure loss calculations
- Easy pre-setting of max design flow using either a special setting key (see accessories) or a standard 7mm wrench
- Angled and straight versions with matching lockshield available.
- Accessories available including towel rail applications
- The valve insert can be exchanged whilst the system is in operation



# Balancing

Balanced systems offer many energy efficiency benefits and increased comfort control over an unbalanced system. For a two- pipe system, the Honeywell Home TRVs offer a smart solution for balancing in an easy and reliable way.




## UNBALANCED HEATING SYSTEM


### Evaluation

Energy efficiency Comfort

LOW HIGH



- Inefficient heating
- Over or underheated rooms
- Decreased room comfort for user



## BALANCED HEATING SYSTEM

### Evaluation

Energy efficiency Comfort

LOW HIGH



- Efficient heating
- Even heat distribution
- Increasing thermal room comfort and user satisfaction

## BALANCING METHODS

Traditionally, one way to balance a radiator is to measure the temperature drop across the radiator and set it to the design temperature drop based on the radiator manufacturer's guidance using the lockshield to adjust temperature.

Alternatively you can open up all of your radiators and record which radiators heat up fastest and balance by adjusting the lockshields, which is quite difficult without enlisting assistance to check the temperature at each radiator.



Balancing key  
VA8201

Balancing insert  
(see product code  
selector for options)

## HONEYWELL HOME TRV BALANCING APP


Honeywell Home TRV balancing app is now available to make balancing simple.

All Honeywell Home TRVs are fitted with an adjustable insert as standard, this insert can be used to balance the system with the added advantage that the TRV can be closed and re-opened without affecting its setting.

By using the Honeywell Home TRV balancing app you only need to balance once.



Scan the QR code to download the Honeywell Home TRV balancing app.



# evohome smart TRVs



## EVOHOME WI-FI MULTI-ZONE SYSTEM

evohome is a sophisticated heating system that ensures you can create and individually control up to 12 heating zones in residential properties. The system also controls hot water, time and temperature.

evohome is suitable for any home with a hydronic (wet) central heating system.

evohome allows you to integrate wet underfloor heating into the main heating control system.

### evohome features

- With touch-screen control, the user can quickly gain control of exactly where and when the property should be heated
- Remote access is provided via a tablet or smartphone
- Wireless radiator controllers provide an easy way of installing heating zones without draining down or disturbing pipes or decor



### HR91 wireless radiator controller

- Fits on most standard TRV bodies
- Battery powered with a two-year battery life
- Basic override button for setting frost protection
- 4 pack available - HR914



### HR92UK wireless radiator controller

- Backlit LCD screen displays zone name and local set point temperature
- Local set point temperature can be overridden by turning the dial
- Fits on most standard TRV bodies
- 4 pack available - HR924UK

## USING EVOHOME



### ATP921R3100

- 1 x evohome controller, power lead, table stand and wireless receiver box
- evohome wireless radiator controller (You need one per radiator in the system)
- HR924UK: 4 x wireless radiator controllers
- HR92UK: Single wireless radiator controller



### ATP926G3001

- evohome essentials pack (1 x base unit, 6 x HR91 wireless radiator controllers)
- Optional extras: HR914: evohome essentials HR91 wireless radiator controllers - 4 pack
- HR91: Single wireless radiator controller




# Commercial TRVs

The V2000 series of TRVs is a range of valves with various flow rate pre-settings designed for pumped two-pipe heating and cooling systems. The V2000 series is perfect for new build and retro-fit applications and ideal for renewable applications such as heat pumps.

Our commercial TRVs are highly accurate and meet the stringent energy efficiency standard of the new EN215

Each valve has a pre-setting facility to adjust the maximum flow to balance the heating circuit. A setting dial at the top of the valve, with six clearly visible values and a setting reference mark, designed to enable simple setting.

## V2000FX Low Flow




- Nominal flow range 10-70 l/hr
- A range of thermostatic radiator valves for balancing pumped two-pipe heating systems with low flow requirements
- A superior regulation performance in low flow applications for better comfort and energy efficiency
- The valves have a quiet operation

## V2000SX Standard Flow



- Nominal flow range 20-170 l/hr
- Standard or reverse flow capability
- A range of thermostatic radiator valves with a wide range of flow rate pre-settings for balancing of pumped two-pipe heating and cooling systems
- The valves have a quiet operation in both standard and reverse flow direction
- Covering a wide range of dimensions, patterns and connections, it offers a solution for almost all installation situations in new building, renovation and retrofit projects

## V2000LX High Flow



- Nominal flow range 20 - 235 l/hr
- A range of thermostatic radiator valves with a stepless pre-settings over a wide range of flow rates for balancing of pumped two-pipe heating and cooling systems with high design flow requirements
- The valve design maximizes the flow rate possibilities of the standard valve bodies, providing an unmatched 2K p-band flows
- The V2000LX are available in straight and angled DN15 and DN20 versions
- High flow capacity makes these versions ideal for use with Heat Pumps, without the need for hydraulic separation

## CAPRI HEAD

### T5019/T5029

The Capri TRV head controls the room temperature by adjusting the flow of hot water through a radiator. Equipped with a liquid filled sensor this delivers 'A' class energy efficiency in accordance to TELL and meets the European Standard EN215 when used with certified Honeywell Home TRV bodies. The compact, stylish modern design is available in white or white and chrome and is a good combination product for the Kombi PI TRV and V2000 series.



## VERAFIX LOCKSHIELD

### V2420

The Verafix-E presettable and drainable lockshield valves can be used in typical two pipe heating systems and in special applications in one pipe heating systems for shut-off and regulation of individual radiators. A draining adaptor can be fitted to the lockshield for draining and filling and the brushed chrome finish matches the Kombi PI TRV and V2000 series.



## TAMPER PROOF HEAD


### T100V

Theft-resistant, heavy duty design, for use in public buildings such as offices, schools, barracks or hospitals.

Compatible with all Honeywell Home radiator thermostats with M30 x 1.5mm connection and 11.5 mm closing dimension.

### Features

- Thermostat resists extreme loads
- Can only be removed with special tool
- Adjustment of the fixed set point with a setting key (T100V-101 and T100VM-101 only)
- Lock disk against unauthorized adjustment (T100V-101 and T100VM-101 only)
- Reliable wax-filled sensing element



# Commercial TRVs

## ROBUST TRV HEAD

### T7000

- Heavy duty and robust version, especially designed for industrial, commercial and public buildings
- Conforms to standard EN 215
- Liquid sensor
- Equipped with memory-clip
- Compatible with all Honeywell Home TRV bodies with M30 x 1.5mm connections



**T7001W0**  
Robust TRV head

**T700120**  
Robust TRV head and sensor

## REMOTE TRV HEAD

### T100MZ

The T100MZ remote TRV sensors are ideal if you want wall mounted external control of radiators that are enclosed.

- Handwheel with socket for wall-mounting
- External liquid-filled sensor with capillary tube
- Easy to read temperature dial
- Compatible with all Honeywell Home TRV bodies with M30 x 1.5mm connections



# Training

**Resideo offer an extensive range of training courses across several platforms to cater to your needs.**

To find out more please visit our Resideo Installer toolbox.  
<https://www.resideoinstallertoolbox.com/resideo-training-toolbox>



# Regulations

## BUILDING REGULATIONS PART L AND PART F FOR DWELLINGS

### Summary of Changes and Timescale

Self regulating devices, aka TRVs are now a requirement of Building Regulations across the UK and have been recognised in policy and regulation for their energy and carbon savings. Tests at Salford University have revealed that TRVs can save up to 18% energy.

For further information on these regulations please scan the QR codes below for the HHIC guide and Beama guide.



HHIC Guide  
<https://www.hhic.org.uk/uploads/5E15C6FD81706.pdf>



BEAMA Guide  
<https://www.beama.org.uk/resourceLibrary/saving-energy-with-heating-controls.html>



# SIMPLY RELIABLE

There's now a **5 year warranty\*** on our most popular Honeywell Home heating controls and Resideo Braukmann water products.

Giving you and your customers peace of mind for years to come.



Find a list of our eligible products at [resideo.com/warranty](https://resideo.com/warranty)

\*Terms and conditions apply  
© 2025 Resideo Technologies, Inc. All rights reserved.  
The Honeywell Home trademark is used under license from Honeywell International Inc.  
This product is manufactured by Resideo Technologies, Inc. and its affiliates.

## Product selector



| DOMESTIC TRVS         |                                                                |
|-----------------------|----------------------------------------------------------------|
| VT15 RANGE            |                                                                |
| VT15AG                | Radiator thermostat 8mm                                        |
| VT15BG                | Radiator thermostat 10mm                                       |
| VT15EG                | Radiator thermostat 15mm                                       |
| VTL15-15A             | TRV & lockshield angled 15mm                                   |
| L15-15A/U             | Lockshield angled 15mm                                         |
| VT120 RANGE           |                                                                |
| VTL120-08A            | TRV & lockshield 8mm angled                                    |
| VTL120-08S            | TRV & lockshield 8mm straight                                  |
| VTL120-10A            | TRV & lockshield 10mm angled                                   |
| VTL120-10S            | TRV & lockshield 10mm straight                                 |
| VTL120-15A            | TRV & lockshield 15mm angled                                   |
| VTL120-15A-D          | TRV & lockshield & drain off 15mm angled                       |
| VTL120-15A-DP         | TRV & lockshield & drain off & push fit 15mm angled            |
| VTL120-15A-P          | TRV & lockshield & push fit 15mm angled                        |
| VTL120-15S            | TRV & lockshield 15mm straight                                 |
| VTL120-15S-D          | TRV & Lockshield & drain off 15mm straight                     |
| VTL120-15S-DP         | TRV & lockshield & drain off & push fit 15mm straight          |
| VTL120-15S-P          | TRV & lockshield & push fit 15mm straight                      |
| VT117-15A             | TRV 15mm angled                                                |
| VT117-15S             | TRV 15mm straight                                              |
| VT200 RANGE           |                                                                |
| VTL200-08A            | TRV & lockshield 8mm angled                                    |
| VTL200-10A            | TRV & lockshield 10mm angled                                   |
| VTL200-10S            | TRV & lockshield 10mm straight                                 |
| VTL200-15A            | TRV & lockshield 15mm angled                                   |
| VTL200-15A-C          | TRV & lockshield 15mm angled chromed                           |
| VTL200-15A-D          | TRV & lockshield & drain of 15mm angled                        |
| VTL200-15A-DP         | TRV & lockshield & drain off & push fit 15mm angled            |
| VTL200-15A-P          | TRV & lockshield & pushfit 15mm angled                         |
| VTL200-15S            | TRV & lockshield 15mm straight                                 |
| VTL200-15S-C          | TRV & lockshield 15mm straight & chromed                       |
| VTL200-15S-D          | TRV & lockshield & drain off 15mm straight                     |
| VTL200-15S-DP         | TRV & lockshield & drain off & push fit 15mm straight          |
| VTL200-15S-P          | TRV & lockshield & push fit 15mm straight                      |
| VT200-15A             | TRV 15mm angled                                                |
| VT200-15S             | TRV 15mm straight                                              |
| MANUAL RADIATOR VALVE |                                                                |
| VHL120-08A            | Manual valve & lockshield 8mm angled                           |
| VHL120-08S            | Manual valve & lockshield 8mm straight                         |
| VHL120-10A            | Manual valve & lockshield 10mm angled                          |
| VHL120-10S            | Manual valve & lockshield 10mm straight                        |
| VHL120-15A            | Manual valve & lockshield 15MM angled                          |
| VHL120-15A-D          | Manual valve & lockshield & drain off 15mm angled              |
| VHL120-15A-DP         | Manual valve & lockshield & drain off & push fit 15mm angled   |
| VHL120-15A-P          | Manual valve & lockshield & push fit 15mm angled               |
| VHL120-15S            | Manual valve & lockshield 15mm straight                        |
| VHL120-15S-D          | Manual valve & lockshield & drain off 15mm straight            |
| VHL120-15S-DP         | Manual valve & lockshield & drain off & push fit 15mm straight |
| VHL120-15S-P          | Manual valve & lockshield & push fit 15mm straight             |

# Product selector



| DESIGNER TRV HEADS |                 |
|--------------------|-----------------|
| T4021GB            | White & chrome  |
| T4111GB            | Brushed chrome  |
| T4221GB            | Polished chrome |
| T4321GB            | Black & chrome  |

| PRESSURE INDEPENDENT TRV |                                                         |
|--------------------------|---------------------------------------------------------|
| V2100API15               | Kombi TRV axial body DN15                               |
| V2100DPI15               | Kombi TRV straight body DN15                            |
| V2100EPI10               | Kombi TRV angled body DN10                              |
| V2100EPI15               | Kombi TRV angled body DN15                              |
| V2100EPI20               | Kombi TRV angled body DN20                              |
| V2100LPI15               | Kombi TRV double angle left body DN15                   |
| V2100RPI15               | Kombi TRV double angle right body DN15                  |
| VTL5100EPI15GB           | Kombi TRV with matching lockshield and 'Capri' TRV head |
| V2100DPI20               | Kombi TRV straight body DN20                            |
| V2420E0015               | Presetable lockshield valve angled DN15                 |
| V2420E0020               | Presetable lockshield valve angled DN20                 |
| V2420D0015               | Presetable lockshield valve straight DN15               |
| V2420D0020               | Presetable lockshield valve straight DN20               |
| T5019W0GB                | Capri TRV head, white                                   |

| PRESSURE INDEPENDENT TRV ACCESSORIES |                                      |
|--------------------------------------|--------------------------------------|
| TA6900A001                           | Theft protection ring for T5019 head |
| FIG1/2CS15                           | Compr fitt for copper / steel 15mm   |
| FIG3/4CS22                           | Compr fitt for copper / steel 22mm   |
| VS1200PI01                           | Kombi PI type valve insert           |

| BALANCING   |                                                                                |
|-------------|--------------------------------------------------------------------------------|
| VA8201PI04  | Kombi TRV metal pre-setting key                                                |
| VA8201TRV01 | Plastic pre-setting key                                                        |
| VS1200SX01  | Replacement valve insert for VT15, VT120, VT200, VT117 & V2000SX Standard Flow |
| VS1200LX01  | Replacement valve insert for V2000LX High Flow                                 |
| VS1200FX01  | Replacement valve insert for V2000FX Low Flow                                  |
| VS1200PI01  | Kombi PI type valve insert                                                     |

| EVOHOME SMART TRVS |                                                       |
|--------------------|-------------------------------------------------------|
| HR91               | Single pack of evohome smart TRV heads                |
| HR914              | 4 pack of evohome smart TRV heads                     |
| HR924UK            | 4 pack of evohome smart TRV heads (with display)      |
| HR92UK             | Single pack of evohome smart TRV heads (with display) |
| ATP921R3100        | evohome connected thermostat                          |
| ATP926G3001        | evohome essentials pack (6 x HR91)                    |

| COMMERCIAL TRVS BODIES |                        |
|------------------------|------------------------|
| V2000FX LOW FLOW       |                        |
| V2000EFX15             | TRV body angled DN15   |
| V2000DFX15             | TRV body straight DN15 |
| V2000AFX15             | TRV body axial DN15    |

# Product selector



| COMMERCIAL TRVS BODIES |                                                 |
|------------------------|-------------------------------------------------|
| V2000SX STANDARD FLOW  |                                                 |
| V2000ESX15             | TRV body angled DN15                            |
| V2000ESX20             | TRV body angled DN20                            |
| V2000DSX15             | TRV body straight DN15                          |
| V2000DSX20             | TRV body straight DN20                          |
| V2000ASX15             | TRV body axial DN15                             |
| V2000BSX15             | TRV body straight DN15 with swan neck tailpiece |

| V2000LX HIGH FLOW |                        |
|-------------------|------------------------|
| V2000ELX15        | TRV body angled DN15   |
| V2020ELX20        | TRV body angled DN20   |
| V2000DLX15        | TRV body straight DN15 |
| V2020DLX20        | TRV body straight DN20 |

| COMMERCIAL TRV ACCESSORIES |                                                  |
|----------------------------|--------------------------------------------------|
| FIG1/2CS15                 | Compr fitt for copper / steel 15mm               |
| FIG3/4CS22                 | Compr fitt for copper / steel 22mm               |
| VA5201A015                 | Radiator tailpiece with thread up to collar DN15 |
| VA5201A020                 | Radiator tailpiece with thread up to collar DN20 |
| VA5201A015                 | Extended radiator tailpiece DN15                 |
| VA5201A020                 | Extended radiator tailpiece DN20                 |


| COMMERCIAL TRV HEADS & LOCKSHIELDS |                                |
|------------------------------------|--------------------------------|
| CAPRI HEAD                         |                                |
| T5019W0GB                          | Capri TRV head, white          |
| T5029W0GB                          | Capri TRV head, white / chrome |

| VERAFIX LOCKSHIELD |                                           |
|--------------------|-------------------------------------------|
| V2420E0015         | Presetable lockshield valve angled DN15   |
| V2420E0020         | Presetable lockshield valve angled DN20   |
| V2420D0015         | Presetable lockshield valve straight DN15 |
| V2420D0020         | Presetable lockshield valve straight DN20 |

| TAMPER PROOF HEAD |                                                  |
|-------------------|--------------------------------------------------|
| T100VM-101        | Heavy duty TRV head with theft protection 6-26°C |
| WT100V            | Special tool to remove T100VM head               |
| AS100VM           | Screw lock for T100VM head. 5 pcs                |
| FS100V            | Lock disk for T100VM head. 5 pcs                 |

| ROBUST TRV HEAD |                                                  |
|-----------------|--------------------------------------------------|
| T700120         | Heavy duty TRV head with 2m remote sensor 6-28°C |
| T7001W0         | Heavy duty TRV head with internal sensor 1-28°C  |
| TA2080A001      | Theft - protection ring for T7001                |

| REMOTE TRV HEAD |                                                     |
|-----------------|-----------------------------------------------------|
| T100MZ-2512     | TRV remote sensing unit 9-26°C, capillary length 2m |
| T100MZ-2515     | TRV remote sensing unit 9-26°C, capillary length 5m |



**For more information**  
[resideo.com](https://resideo.com)

© 2025 Resideo Technologies, Inc. All rights reserved.  
The Honeywell Home trademark is used under license from Honeywell International Inc.  
This product is manufactured by Resideo Technologies, Inc. and its affiliates.

**resideo**