


THERMOSTATS QUICK REFERENCE GUIDE



Connected Thermostats

		Description	Model	Schedule Options			User Interface	Application						Power Method	Features and Functions								Service Reminders	Limited Warranty	Wiring Terminals	Accessories Included															
	Network Connection			Program Options	Temporary Override	Permanent Hold	Vacation Hold		Stages	Gas, Oil or Electric	Heat Pump	750 Millivolt*	Linevolt	Selectable Residential and Commercial	Dual fuel	Balanced Point Lockout	Upstage Timer & Droop Settings	Humidification Control	Dehumidification Control	Ventilation Control		Demand Response	Permanent Memory Retention	Selectable Auto or Manual Changeover	Auxiliary Heat Lockout	Adaptive Intelligent Recovery	Temperature Setpoint Limits	Keypad Lockout	Programmable & Cyclic Fan	Tri-Lingual Language Options	Wireless Outdoor Sensor	Wired Outdoor Sensor	Wired Indoor Sensor	Wireless Indoor Temp/Hum Sensor	Wireless Indoor Motion Sensor	Dealer Info/On Screen	Display Size (Viewable)	Continuous Backlighting	Filter/Humidifier Pad, UV Lamp/Replacement Reminders		
		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor	YTHM1004R3000	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•			24 volt to R and C at thermostat and EIM	•	•	•	•	•		•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	Equipment Interface Module R, C, RH, RC, W, O/B, W/2/AUX1, Y/3/AUX2, Y/Y2, G, L, U1, U1, U2, U2, U3, U3, S1, S2, S3, S4, S4	T10+ Thermostat, THM04R3000 EIM, 2 duct sensors, CT189R300 Wireless Indoor Sensor								
		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor, Wireless Outdoor Sensor	YTHM1004R3001	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•			24 volt to R and C at thermostat and EIM	•	•	•	•	•		•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	Equipment Interface Module R, C, RH, RC, W, O/B, W/2/AUX1, Y/3/AUX2, Y/Y2, G, L, U1, U1, U2, U2, U3, U3, S1, S2, S3, S4, S4	T10+ Thermostat, THM04R3000 EIM, 2 duct sensors, CT189R3002 Wireless Indoor Sensor, C7089R3013 Wireless Outdoor Sensor								
		T10 Pro Smart with RedLINK® Sensor	THX321WFS2001W	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	•	•	•			C-Wire	•	•	•	•	•		•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	R, RC, C, W, 2-AUX, E, O/B, Y, 2, G, L, K, U, U, S and S	CT189R2002 wireless temp/humidity/motion sensor, UWP mounting system, decorative cover plate, & mounting hardware								
		T10 Pro Smart without Sensor	THX321WF2003W	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	•	•	•			C-Wire	•	•	•	•	•		•	•	•	•	•	•	7.27 sq. in.	•	•	5 Year	R, RC, C, W, 2-AUX, E, O/B, Y, 2, G, L, K, U, U, S and S	UWP mounting system, decorative cover plate, & mounting hardware								

*For 750 millivolt thermostats without EIM, 24 volt transformer must wire to Rc and C and heater wires to R and W. For EIM, 24 volts to R and C. Millivolt heater to Rh and W.

For more information
www.resideo.com/pro

resideo

Resideo Technologies, Inc.
16100 N 71st Street, Suite 550
Scottsdale, Arizona 85254
Office: 480.573.5340
resideo.com

50-1376 Visor Card | NM | 01/23
© 2023 Resideo Technologies, Inc. All rights reserved. The Honeywell Home trademark is used under license from Honeywell International, Inc. These products are manufactured by Resideo Technologies, Inc. and its affiliates.

Non-Connected Thermostats

	Description	Model	Scheduling	User Interface	Stages	Application	Power Method	Memory Retention	Selectable Auto or Manual Changeover	Dial Fuel	Sensors	Temperature Limits	Display Information	Limited Warranty	Wiring Terminals	Accessories Included	
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool - Heat Pump Up to 2 Heat/2 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool - Heat Pump Up to 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•			•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E and K	UWP mounting system, decorative cover plate, mounting hardware & batteries
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only - No Fan		Dual powered (battery and hardwire)	•				•	5.44 sq. in.	•	5 Year	R, RC, C, W, S, and S	Floor sensor, UWP mounting system, decorative cover plate, mounting hardware & batteries
	T4 Pro	TH4210U2002	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool - Heat Pump Up to 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•			•	3.93 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E & K	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH4110U2005	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 1 Heat/1 Cool - Heat Pump Up to 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•			•	3.93 sq. in.	•	5 Year	R, RC, W, O/B, Y, G, C, L, and K	UWP mounting system, decorative cover plate, mounting hardware & batteries
	TL8100 Hydronic	TL8100A1008	7-Day	Soft keys	Control a line Voltage (120/240VAC) valve or pump or a 24 volt valve	Gas or oil	Battery powered	•					2.67 sq. in.	•	5 Year	1, 2, 3	Mounting hardware & batteries
	T3 Pro Non-Programmable	TH3210U2004	NP	Soft keys	2 Heat/1 Cool - Heat Pump 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•			•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, G, AUX, and E	UWP mounting system, decorative cover plate, mounting hardware & batteries
		TH3110U2008	NP	Soft keys	1 Heat/1 Cool - Heat Pump 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	•			•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, and G	UWP mounting system, decorative cover plate, mounting hardware & batteries
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft keys	2 Heat/1 Cool - Heat Pump only		Dual powered (battery and hardwire)	•	Manual				1.32 sq. in.	•	5 Year	R, C, O, B, Y, G, L, AUX, and E	Mounting hardware & batteries
		TH3110D1008	NP	Soft keys	1 Heat/1 Cool - Heat Pump 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	Manual				1.32 sq. in.	•	5 Year	R, RC, C, O, B, Y, W, and G	Mounting hardware & batteries
	T1 Pro Non-Programmable	TH1110D2009	NP	Soft keys	1 Heat/1 Cool - Heat Pump 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	Manual			•	2.37 sq. in.	•	5 Year	C, R, RC, W, O/B, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries
	E1 PRO Non-Programmable	TH1110E1000	NP	Soft keys	1 Heat/1 Cool - Heat Pump 1 Heat/1 Cool - Conventional	• • •	Dual powered (battery and hardwire)	•	Manual				3.32 sq. in.	•	2 Year	R, RC, C, W, Y, G, O, and B	Wall-plate, mounting hardware, & batteries
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•						50010944-001	N/A	5 Year	R, W, Y	Mounting hardware	
		T87N1000	NP	Dial	1 Heat/1 Cool	•						50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•						50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
	Econostat Horizontal	T8034N1007	NP	Slide switches and lever	1 Heat/1 Cool	•						50019661-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
	Econostat	T822K1000	NP	Slide switches and lever	1 Heat	•						50019661-001	N/A	5 Year	R, W	Mounting hardware	
		T827K1009	NP	Slide switches and lever	1 Heat	•						50019661-001	N/A	5 Year	R, W	Mounting hardware	
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat		Mechanical						2.67 sq. in.	•	5 Year	4-wire DPST	Mounting hardware
	Line Volt PRO™	TL7235A1003	NP	Horizontal lays	1 Heat		Mechanical						2.67 sq. in.	•	3 Year	4-wire DPST	Mounting hardware
	T410A B Line Voltage Electric Heat	T410A1013 T410A1021 T410B1004	NP	Dial	1 Heat		3238 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off				272804A Range Stop and Loading Cover	N/A	3 Year	T410A - 2-wire SPST T410B - 4-wire DPST	Mounting hardware
	Line Volt 5-2 Programmable	TH105PLUS	5-2	Buttons	1 Heat		3500 watts @ 240 VAC Max 1700 watts @ 120 VAC Max	•				•		•	3 Year	2-wire SPST	Mounting hardware